FORM PTO-1390 (REV. 11-2000) U S DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE ATTORNEY'S DOCKET NUMBER TRANSMITTAL LETTER TO THE UNITED STATES 33388 DESIGNATED/ELECTED OFFICE (DO/EO/US) US APPLICATION NO. (If known, see 37 CFR 15 CONCERNING A FILING UNDER 35 U.S.C. 371 INTERNATIONAL APPLICATION NO. INTERNATIONAL FILING DATE PRIORITY DATE CLAIMED PCT/JP00/04995 26 July 2000 (26.07.00) 29 July 1999 (29.07.99) TITLE OF INVENTION FOLDABLE MOBILE COMMUNICATION TERMINAL APPLICANT(S) FOR DO/EO/US HAYASHI, Takahiro; KUBO, Tetuya Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information: 1. X This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below. The US has been elected by the expiration of 19 months from the priority date (Article 31). 5. X A copy of the International Application as filed (35 U.S.C. 371(c)(2)) is attached hereto (required only if not communicated by the International Bureau). has been communicated by the International Bureau. is not required, as the application was filed in the United States Receiving Office (RO/US). An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). is attached hereto. has been previously submitted under 35 U.S.C. 154(d)(4). Amendments to the claims of the International Aplication under PCT Article 19 (35 U.S.C. 371(c)(3)) are attached hereto (required only if not communicated by the International Bureau). b. have been communicated by the International Bureau. have not been made; however, the time limit for making such amendments has NOT expired. d. X have not been made and will not be made. An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)). An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. An English lanugage translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). Items 11 to 20 below concern document(s) or information included: An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 11. X An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 12. X A FIRST preliminary amendment. A SECOND or SUBSEQUENT preliminary amendment. 15. A substitute specification. 16. A change of power of attorney and/or address letter. A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. 17. A second copy of the published international application under 35 U.S.C. 154(d)(4). 18. A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 19. \square 20. 🗓 Other items or information: International Search Report

U.S. APPLICATION NO. (if to	Win see 37 CFR 1 5)		ERNATIONAL APPLICATION NO JP00/04995			ATTORNEY'S DOG 33388	CKET NUMBER
	ing fees are subm	itted:			CAL		PTO USE ONLY
BASIC NATIONAL	_		1) - (5)):				
Neither internation nor international se and International S	al preliminary exa earch fee (37 CFR earch Report not p	amination 1.445(a) prepared	n fee (37 CFR 1.482) (2)) paid to USPTO by the EPO or JPO	\$1000.00			
International prelim USPTO but Interna	ninary examinatio ational Search Rej	n fee (37 port prep	CFR 1.482) not paid to ared by the EPO or JPO	\$860.00			
International prelin but international se	ninary examinatio arch fee (37 CFR	n fee (37 1.445(a)	CFR 1.482) not paid to (2)) paid to USPTO	USPTO \$710.00			
			CFR 1.482) paid to US T Article 33(1)-(4)				
and all claims satis	fied provisions of	PCT An	CFR 1.482) paid to US ticle 33(1)-(4)	\$100.00			
			BASIC FEE AMOU	JNT =	\$	860.00	
Surcharge of \$130.0 months from the ear	0 for furnishing the liest claimed prior	ne oath o rity date	r declaration later than (37 CFR 1.492(e)).	<u>20</u> 30	\$		
CLAIMS	NUMBER FIL	ED	NUMBER EXTRA	RATE	\$		
Total claims	16 -20	==	0	x \$18.00	\$		
Independent claims	2 -3		00	x \$80.00	\$		
MULTIPLE DEPEN		<u> </u>		+ \$270.00	\$	270.00	
Total			<u>F ABOVE CALCU</u>		\$ 1	,130.00	
Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.							
SUBTOTAL =					\$ 1	,130.00	
Processing fee of \$1 months from the ear	30.00 for furnishi liest claimed prior	ng the E	` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `		\$	***	
\$			TOTAL NATIO		\$ 1	,130.00	
accompanied by an	e enclosed assigni appropriate cover	ment (37 sheet (37	CFR 1.21(h)). The assi 7 CFR 3.28, 3.31). \$40.0	gnment must be 00 per property +	\$	40.00	
			TOTAL FEES E	NCLOSED =	\$ 1	,170.00	
						ount to be refunded:	\$
						charged:	\$
			0.00 to cover th			4	1
A duplicate	b. Please charge my Deposit Account No in the amount of \$ to cover the above fees. A duplicate copy of this sheet is enclosed.						
c. X The Comm overpayme	issioner is hereby nt to Deposit Acc	ount No.	ted to charge any addition 16-0820. A duplicated No. 33388	nal fees which may b ate copy of this sheet	e requ is enc	ired, or credit a losed.	any
d. Fees are to information	be charged to a cr n should not be i	edit card	. WARNING: Information this form. Provide of	ation on this form mag credit card information	y beco	me public. Cr authorization o	edit card n PTO-2038.
NOTE: Where an 1.137 (a) or (b)) m	appropriate timust be filed and g	e limit u ranted t	nder 37 CFR 1,494 or 1 o restore the applicatio	.495 has not been non to pending status.	let,/a 1	petition to revi	ive (37 CFR
SEND ALL CORRESPO			••	1/1	len.	111 1	//
Jeffrey J.				Jak J	nui	MICHE	
Pearne & Go				SIGNATIO	RE /	/ /	
	or Avenue Eas		ite 1200		ey Ĵ	Sopko	******************************
Cleveland,	Ohio 44114-1	.484		NAME			
				27676			
				REGISTR	ATION	NUMBER	

"EXPRESS MAIL" MAILING LABEL CERTIFICATE

Re: U.S. PCT-based Patent Application for "FOLDABLE MOBILE COMMUNICATION TERMINAL"

International Application No.: PCT/JP00/04995

International Filing Date: July 26, 2000

Attorney's Docket No.: 33388

"Express Mail" mailing label number <u>EL595432311US</u>

Date of Deposit 3/28/01

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

<u> Janet Morrison</u>

Printed Name of Person Mailing Paper or Fee

Signature of Person Mailing Paper or Fee

25

JG08 Rec'd PCT/PTO 28 MAR 2001

DESCRIPTION

FOLDABLE MOBILE COMMUNICATION TERMINAL

5 Technical Field

The present invention relates to a mobile communication terminal constructed in such a manner that the upper case and the lower case can be folded one on another by means of a hinge, and more specifically, to a mobile communication terminal wherein the number of wiring between the upper case and the lower case is reduced and the components are arranged so as to reduce the thickness of the lower case and the lower case.

Background Art

In general, a mobile communication terminal that can be folded by means of a hinge as in Fig. 10 and Fig. 11 is known.

Fig. 10 shows the first example of the relatedart, wherein Fig. 10A is a plan view showing the opened state with the case portions removed, the upper portion of the figure illustrates the upper case side and the lower portion illustrates the lower case side, and Fig. 10B is a side view with the case portions removed.

The upper case side in Fig. 10 is constructed in such a manner that an antenna 41 and a liquid crystal display 42 are provided, and a control function block and a function block corresponding to the display is mounted on the logical printed

25

5

board 43. The lower case side in Fig. 10 is provided with a switch 47 for key-in operation, a function block corresponding to the switch, a RX printed board 48 for mounting a function blockforcontrolling the radio communication (RX), and a battery 46. In order to connect the upper and lower function blocks, a coaxial cable 44 and a flexible connector 45 are provided.

Fig. 11 is the second example of the related art, wherein Fig. 11A is a plan view showing the opened state with the case portions removed, and on the lower portion, switches for key-in operation 56 that enable a key-in operation of the key board arranged on the upper portion in the closed state are arranged on the key board 57.

While the lower portion in Fig. 11 constitutes a flip portion with switches for key-in operation 56 disposed on the key board 57, the upper portion in Fig. 11 is constructed in such a manner that an antenna 51, a liquid crystal display 52, and a battery 53 are provided, and the main printed board 54 is mounted with function blocks corresponding thereto and a function block for controlling the radiocommunication (RX) and the logical control. A flexible connector 55 for electrically connecting the upper portion and the lower portion is also provided.

In the mobile communication terminal, there has been a requirement that a slim profile as well as lightweight and downsizing are realized because the weight, size and thickness of the equipment as a whole are evaluated as an important indicator of the mobilability.

2.5

However, in the first example of the related art, the conventional hard printed board is used for each of the upper case and the lower case, and a coaxial cable of conventional type is used as a cable for connecting the upper and lower cases. Therefore, the weight and the thickness of the equipment as a whole, being apart from downsizing, are still remaining as a subject to be solved.

In the second example of the related art, since it has only a flip construction and the upper and lower cases cannot be folded one on another, there has been such problem as regards the weight balance that it is heavier on the upper portion, thereby lacking in weight balance.

Accordingly, it is an object of the present invention to provide a foldable mobile communication terminal in which the number of wiring between the upper case and the lower case is reduced, and the components are arranged so as to reduce the thickness of the upper case and the lower case.

Disclosure of the Invention

According to the first aspect of the present invention, the control section, the display, the RF communication section, the I/O section and the vibrator section of which the function block is mounted on the hard board are arranged and accommodated in the upper case, and the operation section and the battery of which the function block is mounted on the key board are arranged and accommodated in the lower case, whereby the compact and the slim profile is realized by reducing the number of wiring

25

5

for connecting the upper and lower cases by arranging these functions together in the function blocks to be accommodated in the upper and lower cases, and by mounting only the components corresponding to the key-in operation and the battery on the board in the lower case.

According to the second aspect of the present invention, the display arranged and accommodated in the upper case comprises a liquid crystal display, and a menu selecting section for selecting a menu by navigating through the menu system displayed on the display is disposed in the vicinity of lower side of the display, whereby the operability is improved by arranging the menu selecting section in the vicinity of the display.

According to the third aspect of the present invention, the key board arranged and accommodated in the lower case is a flexible board, and the flexible board is shared its use with the connecting board for connecting the upper case and the lower case, whereby the usage of the flexible board contributes to achieve further compact and slim profile.

According to the fourth aspect of the present invention, the battery terminal, the microphone, the key diaphragm, and the LED for keys are all mounted on the same surface of the flexible board and folded or turned down before storing in the lower case, wherebypackaging of those components on the flexible board can be facilitated and further compact and slim profile is realized by putting some thought into the storage in the lower case

According to the fifth aspect of the invention, the

25

5

microphone is mounted in an inclined state on the lower side of the lower case at the position close to the mouth so as to receive the sound from the speaker directly while in use, whereby the sound collecting property of the microphone is improved and the space to which the microphone is mounted is secured while saving the space.

According to the sixth aspect of the invention, a view port is provided on the lower case so that the contents displayed on the display can be seen in the folded state, whereby the displayed content can be seen in the folded state.

According to the seventh aspect of the invention, the view port is disposed between the microphone and the operation section, whereby the displayed contents can be seen conveniently in the closed state.

According to the eighth aspect of the invention, the view port is provided with a transparent plate, whereby the displayed contents can be seen while preventing the dust from entering therein.

According to the ninth aspect of the invention, the transparent plate is given a lens function, whereby the displayed contents can be enlarged.

According to the tenth aspect of the invention, the portion of the upper case and the lower case in the vicinity of the portion being mechanically connected with respect to each other is formed in a narrower configuration than the remaining portion, whereby the gripping property in the opened state is enhanced and the total weight is reduced.

According to the eleventh aspect of the invention, the control section, the display, and the RF communication section of which the function blocks are mounted on the hard board are arranged and accommodated in the upper case, and the operation section, the I/O connector, the vibrator of which the function blocks are mounted on the key board and the battery are arranged and accommodated in the lower case, whereby the number of wiring is reduced by bringing the function blocks to be arranged in the upper and lower cases respectively closer by function, and only the components corresponding to the control section, the display, and the RF communication section are mounted on the hard board in the upper case, thereby realizing further compact and slim profile of the upper case.

According to the twelfth aspect of the invention, the flexible board is used as the key board arranged and accommodated in the lower case, and the flexible board is shared its use with the connecting board connecting the upper case and the lower case, whereby further compact and slim profile is realized by employment of the flexible board.

According to the thirteenth aspect of the invention, the battery terminal, the vibrator, the microphone, the buzzer, the key diaphragm, and the LED for keys are all mounted on the same surface of the flexible board and folded or turned down before storing in the lower case, whereby further compact and slim profile is realized by putting some thought into the storage in the lower case.

According to the fourteenth aspect of the invention, the

portion of the upper case and the lower case near the portion being mechanically connected with respect to each other formed in a narrower configuration than the remaining portion, whereby the gripping property in opened state is enhanced and the total weight is reduced.

Brief Description of the Drawings

- Fig. 1 is a perspective view of a foldable mobile communication terminal in the opened state according to the first embodiment of the present invention.
- Fig. 2 is a rear perspective view of a foldable mobile communication terminal in the opened state according to the first embodiment of the present invention.
- Fig. 3 is a side view of a foldable mobile communication terminal in the opened state according to the first embodiment of the present invention.
- Fig. 4 is a side cross sectional view of a foldable mobile communication terminal in the closed state according to the first embodiment of the present invention.
- 20 Fig. 5 is a cross sectional plan view showing an electrical connection between the upper case and the lower case and a general construction of a flexible board on which the function block for the components to be arranged in the lower case.
- Fig. 6 is a perspective view of a foldable mobile communication terminal in the opened state according to the second embodiment of the present invention.
 - Fig. 7 is a rear perspective view of the foldable mobile

5

communication terminal in the opened state according to the second embodiment of the present invention.

Fig. 8 is a sectional side elevation of the foldable mobile communication terminal in the closed state according to the second embodiment of the present invention.

Fig. 9 is a plan sectional view showing an electric connection between the upper case and the lower case, and a general construction of the flexible board on which a functional block for the components to be arranged in the lower case.

Fig. 10 is a block diagram showing the interior of the mobile communication terminal that can be folded by means of a hinge according to the first example of the related art.

Fig. 11 is a block diagram showing the interior of the mobile communication terminal that can be folded by means of a hinge according to the second example of the related art.

Embodiments of the Invention

(First Embodiment)

Referring now to Fig. 1 to Fig. 5, the first embodiment of the present invention will be illustrated.

Fig. 1 is a perspective view of the foldable mobile communication terminal in the opened state according to the first embodiment of the present invention; Fig. 2 is a rear perspective view of the foldable mobile communication terminal in the opened state according to the first embodiment of the present invention; Fig. 3 is a side view of the foldable mobile communication terminal in the opened state according to the

20

25

5

first embodiment of the present invention; Fig. 4 is a side cross sectional view of the foldable mobile communication terminal in the closed state according to the first embodiment of the present invention; and Fig. 5 is a cross sectional plan view showing an electrical connection between the upper case and the lower case and a general construction of a flexible board on which the function block for the components to be arranged in the lower case.

The foldable mobile communication terminal of the present invention may, as shown in Figs. 1 to 5, be folded by means of a hinge portion 16 between the upper case 11 and the lower case 12. In the foldable mobile communication terminal of the present invention, function blocks are arranged accommodated in the upper case 11 and the lower case 12 while bringing them closer by function.

In other words, the control section (microcomputer) (not shown), the display (liquid crystal display) 14, the RF communication section (not shown), the buzzer 21, the vibrator 22, the speaker 30, and the I/O connector 24 of which the function blocks are mounted on the hard board 27 are arranged and accommodated in the upper case 11, and the key operation section 18 of which the function block is mounted on the key board (flexible board 28) and the battery 29 are arranged and accommodated in the lower case 12.

Consequently, an antenna 13 is arranged on the upper case 11 which includes the RF communicating section (not shown), and the key operation section 18 and the battery 29 are arranged

and accommodated in the lower case 12, so that it is not necessary any more to construct in such a manner that the antenna 41 is arranged on the upper case, a connecting passage for supplying a power or for transmitting signals to the antenna 41 is provided through the logical printed board 43 and the coaxial cable 44, and the function blocks for the battery 46 and the RF communicating section are mounted on the RX printed board 48, which is a hard board, in the lower case, as is in the first example of the related art shown in Fig. 10. In addition, balanced arrangement of the components in the upper and lower cases reduces the power required of the vibrator and the length of the electrical wiring of the I/O connector in comparison with the case where majority of components are arranged in the upper case as shown in the second example of the related art, thereby realizing further compact and slim profile.

The foldable mobile communication terminal of the present invention is provided with a menu selecting section 15 for selecting a suitable menu by navigating through the menu system while viewing contents displayed in the display 14, for example, a menu screen in the vicinity of the lower side of the display 14. In this arrangement, operability in navigative selection can be improved. In relation to the menu selecting section 15, it is also possible to provide a operating keys such as a mode key, a telephone number list key, and a menu key on both sides of the menu selecting section 15, though they are not specified in the figure.

The foldable mobile communication terminal according to

25

the present invention uses a key board arranged and accommodated in the lower case 12 as a flexible board 28, as shown in Fig.

- 5. The flexible board 28 is shared its use with the connecting board for connecting the upper case 11 and the lower case 12.
- In this way, according to the present invention, since the flexible board 28 is employed and thus the RX printed board 48, which is a hard board, is not employed in the lower case as in the first example of the related art shown in Fig. 10, further compact and slim profile is realized.

In the flexible board 28 of the present invention, components such as the battery terminal 58, the microphone 20, the key diaphragm, and the LED for key display to be arranged and accommodated in the lower case is mounted on the same surface of the flexible board 28 and folded or turned down before storing in the lower case. In other words, some components to be mounted are folded along the folding portion 31 before storing in the lower case as shown in Fig. 5, so as to facilitate packaging of those components on the flexible board 28 and to realize further compact and slim profile by putting some thought into the storage in the lower case.

In addition, the foldable mobile communication terminal of the present invention is provided with a narrowed portion 17 on the upper case 11 and the lower case 12 near the hinge portion 16. In this arrangement, the user can hold near the narrowed portion 17 when he or she opens and uses the mobile communication terminal, the narrowed portion enhances the gripping property, and in addition, reduces the total weight

20

25

5

of the terminal since the narrowed portion 17 is formed and thus the portion of the case member corresponding to the narrowed portion 17 is eliminated.

According to the foldable mobile communication terminal of the present invention, since a view port 19 is provided, the contents of the display 14 can be seen in the closed state as shown in Fig. 4. The view port 19 can be formed in a through port or provided with a transparent plate. In this case, when the transparent plate is formed by a lens, the displayed contents can be enlarged and the transparent plate can prevent dust from entering inside in the closed state.

According to the foldable mobile communication terminal, a microphone 20 is mounted in an inclined state on the lower side of the lower case 12. In other words, as shown in Fig. 3, the microphone 20 is mounted in an inclined state on the lower side of the lower case 12, it comes to the closest position to the mouth of the speaker when it is opened (in use), thereby receiving the sound from the speaker directly. Though the microphone 20 and the speaker 30 are, in the closed state, brought closer forming a prescribed angle as shown in Fig. 4, there is no possibility of the occurrence of howling and of the interruption of a ringing signal, if it rings, coming out from the speaker 30 since the microphone 20 is constructed so as not to be energized in the closed state.

Since the HSJ (head set jack) 23 or the side surface operating key 25 are also shown in Fig. 2, Fig. 3 and Fig. 4 in relation to the present invention, they are not recognized

20

25

to be a part of this invention, and thus the description is not given here.

(Second Embodiment)

Referring now to Fig. 6 to Fig. 9, the second embodiment of the present invention will be illustrated.

Fig. 6 is a perspective view of a foldable mobile communication terminal in the opened state according to the second embodiment of the present invention; Fig. 7 is a rear perspective view of the foldable mobile communication terminal in the opened state according to the second embodiment of the present invention; Fig. 8 is a sectional side elevation of the foldable mobile communication terminal in the closed state according to the second embodiment of the present invention; and Fig. 9 is a plan sectional view showing an electric connection between the upper case and the lower case, and a general construction of the flexible board on which a functional block for the components to be arranged in the lower case.

The foldable mobile communication terminal of the present invention can be folded by means of the hinge portion 116 between the upper case 111 and the lower case 112 as shown in Fig. 6 to Fig. 9. In the foldable mobile communication terminal of the present invention, the function blocks are arranged and accommodated in the upper case 111 and the lower case 112 while bringing the function blocks closer by function.

In other words, the components such as the control section (microcomputer) (not shown), the display (liquid crystal display) 114, and the RF communication section (not shown) of

25

which the function blocks are mounted on the hard board 127 are arranged and accommodated within the upper case 111, and the key operation section 118, the I/O connector section 120, the vibrator 132 of which the function blocks are mounted on the key board (flexible board 128) and a battery 129 are arranged and accommodated in the lower case 112.

Consequently, an antenna 113 is disposed on the upper case 111 having the RF communication section (not shown), and the key operation section 118 and the I/O connector section 120, a vibrator 132 and the battery 129 are arranged and accommodated within the lower case 112, so that it is not necessary any more to construct in such a manner that the antenna 141 is arranged on the upper case, a connecting passage for supplying a power or for transmitting signals to the antenna 141 is provided through the logical printed board 143 and the coaxial cable 144, and the function blocks for the battery 146 and the RF communicating section are mounted on the RX printed board 148, which is a hard board, in the lower case, as is in the first example of the related art shown in Fig. 10.

Since the vibrator 132 and the I/O connector section 120 are arranged and accommodated in the lower case 112, the weight balance is improved in comparison with the case where the vibrator (not shown) and the I/O connector (not shown) are all arranged in the upper case as seen in the second example of the related art, whereby the power required of the vibrator is reduced and the compact and slim profile is realized.

The foldable mobile communication terminal according to

the second embodiment of the present invention, as shown in Fig. 9, the flexible board 128 is used as the key board arranged and accommodated in the lower case 112, and the flexible board 128 is shared its use with the connecting board connecting the upper case 111 and the lower case 112. In this way, since the flexible board 128 is employed in this invention, and thus the RX printed board 148, which is a hard board, is not mounted in the lower case as in the first example of the related art shown in Fig. 10, further compact and slim profile can be realized.

In the flexible board 128 of the present invention, the components such as the buzzer 134, the battery terminal 133, the vibrator 132, the microphone 119, the key diaphragm, and the LED for key display (not shown) to be arranged and accommodated in the lower case are all mounted on the same surface of the flexible board 128 and folded or turned down before storing in the lower case. In other words, as shown in Fig. 9, some components to be mounted are folded along the folding portion 131 before storing in the lower case, so as to facilitate packaging of those components on the flexible board 128 and realize further compact and slim profile by putting some thought into the storage in the lower case.

In addition, the foldable mobile communication terminal of the present invention is provided with a narrowed portion 117 on the upper case 111 and the lower case 112 near the hinge portion 116. In this arrangement, the user can hold near the narrowed portion 117 when he or she opens and uses the mobile

25

communication terminal, the narrowed portion enhances the gripping property, and in addition, reduces the total weight of the terminal since the narrowed portion 117 is formed and thus the portion of the case member corresponding to the narrowed portion 117 is eliminated.

Though the menu selecting section 115 is provided on the upper portion of the lower case 112 in the example shown in Fig. 6, it is also possible to provide it in the vicinity of the lower portion of the display 114 on the upper case 111. In this arrangement, since it is located immediately near the display 114, operability in navigative selection can be improved.

Industrial Applicability

As will be understood by the description above, according to the present invention, the control portion, the display, the RF communication section, the I/O section and the vibrator section of which the function blocks are mounted on the hard board are arranged and accommodated in the upper case, the operation section and the battery storage for storing a battery of which the function block is mounted on the key board and accommodated in the lower case, and thus there is an advantage in that the compact and slim profile is realized by reducing the number of wiring for connecting the upper and lower cases by arranging these functions together in the function blocks to be accommodated in the upper and lower cases, and by mounting only the components corresponding to the key-in operation and

15

20

25

the battery on the board in the lower case.

According to the present invention, the display arranged and accommodated in the upper case comprises a liquid crystal display, and a menu selecting section for selecting a menu by navigating through the menu system displayed on the display is disposed in the vicinity of lower side of the display, whereby there is an advantage in that the operability is improved by arranging the menu selecting section in the vicinity of the display.

According to the present invention, the keyboard arranged and accommodated in the lower case is a flexible board, and the flexible board is shared its use with the connecting board for connecting the upper case and the lower case, whereby there is an advantage in that the usage of the flexible board contributes to achieve further compact and slim profile.

According to the present invention, a battery terminal, a microphone, a key diaphragm, and a LED for keys are all mounted on the same surface of the flexible board and folded or turned down before storing in the lower case, whereby there is an advantage in that packaging of those components on the flexible board can be facilitated and further compact and slim profile is realized by putting some thought into the storage in the lower case.

According to the present invention, the microphone is mounted in an inclined state on the lower side of the lower case at the position close to the mouth so as to receive the sound from the speaker directly while in use, whereby there

20

25

is an advantage in that the sound collecting property of the microphone is improved and the space to which the microphone is mounted is secured while saving the space.

According to the present invention, a viewport is disposed on the lower case so that the contents displayed on the display can be seen in the folded state, whereby there is an advantage in that the displayed contents can be seen in the folded state.

According to the present invention, the view port is disposed between the microphone and the operation section, whereby there is an advantage in that the displayed contents can be seen conveniently in the closed state.

According to the present invention, a transparent plate is mounted on the view port, whereby there is an advantage in that the displayed contents can be seen while preventing the dust from entering therein.

According to the present invention, the transparent plate is given a lens function, whereby there is an advantage in that the displayed contents can be enlarged.

According to the present invention, the portion of the upper case and the lower case in the vicinity of the portion being mechanically connected with respect to each other is formed in a narrower configuration than the remaining portion, whereby there is an advantage in that the gripping property in the opened state is enhanced and the total weight is reduced.

According to the present invention, the control section, the display, and the RF communication section of which the function blocks are mounted on the hard board are arranged and

20

25

5

accommodated in the upper case, and the operation section, the I/O connector, the vibrator and the battery of which the function blocks are mounted on the key board are arranged and accommodated in the lower case, whereby there is an advantage in that the number of wiring is reduced by bringing the function blocks to be arranged in the upper and lower cases respectively closer by function, and only the components corresponding to the control section, the display, and the RF communication section are mounted on the hard board in the upper case, thereby realizing further compact and slim profile of the upper case.

According to the present invention, the flexible board is used as the key board arranged and accommodated in the lower case, and the flexible board is shared its use with the connecting board connecting the upper case and the lower case, whereby there is an advantage in that further compact and slim profile is realized by employment of the flexible board.

According to the present invention, the battery terminal, the vibrator, the microphone, the buzzer, the key diaphragm, and the LED for keys are all mounted on the same surface of the flexible board and folded or turned down before storing in the lower case, whereby there is an advantage in that further compact and slim profile is realized by putting some thought into the storage in the lower case.

According to the present invention, the portion of the upper case and the lower case near the portion being mechanically connected with respect to each other formed in a narrower configuration than the remaining portion, whereby there is an advantage in that the gripping property in opened state is enhanced and the total weight is reduced.

CLAIMS

- 1. A foldable mobile communication terminal comprising:
- an upper case including a control section, a display, a RF communication section, an I/O section and a vibrator section of which a function block is mounted on a hard board are arranged; and
- a lower case including a operation section and a battery

 of which a function block is mounted on the key board.
 - 2. A foldable mobile communication terminal according to claim 1,

wherein the display arranged and accommodated in the upper case comprises a liquid crystal display,

wherein a menu selecting section for selecting a menu by navigating through the menu system displayed on the display is disposed in the vicinity of lower side of the display.

20 3. A foldable mobile communication terminal according to claim 1,

wherein the key board arranged and accommodated in the lower case is a flexible board,

wherein said the flexible board is shared its use with the connecting board for connecting the upper case and the lower case.

15

- 4. A foldable mobile communication terminal according to claim 1, wherein a battery terminal, a microphone, a key diaphragm, and a LED for keys are all mounted on the same surface of the flexible board and folded or turned down before storing in the lower case.
- 5. A foldable mobile communication terminal according to claim 1, wherein the microphone is mounted in an inclined state on the lower side of the lower case at the position close to the mouth so as to receive the sound from the speaker directly while in use.
- 6. A foldable mobile communication terminal according to claim 1, wherein a view port is provided on the lower case whereby the displayed contents on the display can be seen in the folded state.
- 7. A foldable mobile communication terminal according to claim 6, wherein the view port is disposed between the microphone and the operation section.
- 8. A foldable mobile communication terminal according to claim 6 or claim 7, wherein a transparent plate is mounted on the view port.
 - 9. A foldable mobile communication terminal according

25

to claim 8, wherein the transparent plate is given a lens function.

- 10. A foldable mobile communication terminal according to claim 1, wherein the portion of the upper case and the lower case in the vicinity of the portion being mechanically connected with respect to each other is formed in a narrower configuration than the remaining portion.
- 10 11. A foldable mobile communication terminal comprising:

an upper case including a control section, a display, and the RF communication section of which the function blocks are mounted on the hard board; and

- a lower case including a operation section, the I/O connector, the vibrator and the battery of which the function blocks are mounted on the key board.
- 12. A foldable mobile communication terminal according20 to claim 11,

wherein the flexible board is used as the key board arranged and accommodated in the lower case,

wherein the flexible board is shared its use with the connecting board connecting the upper case and the lower case.

13. A foldable mobile communication terminal according to claim 11, wherein the components such as the battery terminal,

the vibrator, the microphone, the buzzer, the key diaphragm, and the LED for keys are all mounted on the same surface of the flexible board and folded or turned down before storing in the lower case.

5

10

14. A foldable mobile communication terminal according to claim 11, wherein the portion of the upper case and the lower case near the portion being mechanically connected with respect to each other formed in a narrower configuration than the remaining portion.

24

ABSTRACT

The components such as a control section (microcomputer) (not shown), a display (liquid crystal display) (14), and RF communication section (not shown) of which the function blocks are mounted on the hard substrate (27) are arranged and accommodated within the upper case (11), and the key operation section (18) of which the function blocks are mounted on the key board (flexible board (28)), and a battery (29) are arranged and accommodated in the lower case (12). Consequently, an antenna (13) is disposed on the upper case (11) having the RF communication section (not shown), and the key operation section (18) and the battery (29) are arranged and accommodated within the lower case (12), so that a slim profile as well as lightweight and downsizing are realized by bringing the function blocks to be arranged and accommodated in the upper case and the lower case closer by function in contrast to the example of the related art.

FIG. 1




FIG. 2





FIG. 3








FIG. 5



6/10






FIG. 8




FIG. 9




FIG. 10A





FIG. 10B



10/10

FIG. 11A





FIG. 11B



	$s box \rightarrow +$	Palent and Tra		JSG THOUGH 9/30/98, OMB 0651-00. U.S. DEPARTMENT OF COMMER				
r the Paperwork Reduction Act	of 1995, no persons are required			contains a valid OMB control numb				
		Attorney Docket Numb	er 333	88				
DECLARA	TION FOR	First Named Inventor	Tak	ahiro Hayashi				
UTILITY O	R DESIGN	COMPLETE IF KNOWN						
	PPLICATION	Application Number						
		Filing Date						
Declaration OR Submitted	Declaration Submitted after	Group Art Unit	Group Art Unit					
with Initial Filing	Initial Filing	Examiner Name						
As a below named inventor	, I hereby declare that:							
My residence, post office add	ress, and citizenship are as stated	i below next to my name.						
•			Cort and injulie	worlds of alumi sames are listed				
	t and sole inventor (if only one na which is claimed and for which a p			womor (a platar names are leach				
FOLDAE	BLE MOBILE COMM	IIINTCATTON TERM	TMAT.					
FOLDAL	TE MODILE COM	IONICATION IEM	TIMAL					
,								
	(Тию	of the Invention)						
the specification of which								
is attached hereto								
OR .								
was filed on (MM/DD/YYY) July/26/2000 as United States Application Number or PCT International								
Application Number PCT	2/JP00/04995 and v	was amended on (MWDD/YYYY)		(d applicab				
L	viewed and understand the conten	us of the phone idealfied speeds	ntion including	the chime as amended by any				
amendment specifically refe		its of the above identified specific	anon, meadang	me cams, as amended by any				
I acknowledge the district of	sclose information which is materi	al to natentability as defined in Tr	tio 37 Code of I	Federal Regulations §1.56				
1 acknowledge the duty to dr	scose information which is traten	ar to paternaomy as denired in 1		coerar regulations, 31.50.				
	PCT international application with		nlry other than	application(s) for patent or inventor the Unted States of America, liste entiticate, or of any PCT internation				
	d beart, by checking me box, a							
below and have also identifie	before that of the application on	ny foreign application for patent						
below and have also identifie application having a filing date		ny foreign application for patent	Priority Not Claimed	Certified Copy Attached? YES NO				
below and have also identifie application having a filing date Prior Foreign Application Number(s)	e before that of the application on Country	ny foreign application for patent which priority is claimed. Foreign Filling Date	Priority	YES NO				
below and have also identified application having a filing date. Prior Foreign Application Number(s) P. Hei.	e before that of the application on	ny foreign application for patent which priority is daimed. Foreign Filling Date (MM/DD/YYYY)	Priority Not Claimed	YES NO				
below and have also identified application having a filing date. Prior Foreign Application Number(s) P. Hei. 11-215521	Country Japan	ny foreign application for patent which priority is daimed. Foreign Filling Date (MM/DDAYYY) July/29/	Priority Not Claimed	YES NO				
below and have also identified application having a filing date of the foreign Application Number(s) P. Hei. 11-215521 P. Hei.	e before that of the application on Country	ry foreign application for patent which priority is daimed. Foreign Filling Date (MM/DD/YYY) July/29/ 1999	Priority Not Claimed	YES NO				
below and have also identified application having a filing date of the foreign Application Number(s) P. Hei. 11-215521 P. Hei.	Country Japan	ry foreign application for patent which priority is daimed. Foreign Filling Date (MM/DDAYYY) July/29/ 1999 July/29/	Priority Not Claimed	YES NO				
below and have also identified application having a filing date of the foreign Application Number(s) P. Hei. 11-215521 P. Hei.	Country Japan	ry foreign application for patent which priority is daimed. Foreign Filling Date (MM/DDAYYY) July/29/ 1999 July/29/	Priority	YES NO				
below and have also identified application having a filing date of the prior Foreign Application Number(s) P. Hei. 11-215521 P. Hei. 11-215522	Country Japan	ry foreign application for patent which priority is daimed. Foreign Filing Date (MM/DD/YYY) July/29/ 1999 July/29/ 1999	Priority Not Claimed	YES NO				
below and have also identified application having a filing date. Prior Foreign Application Number(s) P. Hei. 11-215521 P. Hei. 11-215522 Additional foreign application application number(s)	Country Japan Japan	ry foreign application for patent which priority is daimed. Foreign Filling Date (MM/DDAYYY) July/29/ 1999 July/29/ 1999 Juney/29/ 1999	Priority Not Claimed	YES NO				
below and have also identified application having a filing date. Prior Foreign Application Number(s) P. Hei. 11-215521 P. Hei. 11-215522 Additional foreign application application number(s)	Japan Japan Japan Japan Japan Japan Japan	ry foreign application for patent which priority is daimed. Foreign Filling Date (MM/DDAYYY) July/29/ 1999 July/29/ 1999 Juney/29/ 1999	Priority Not Claimed	YES NO X X X X X X X X X				
below and have also identified application having a filing date. Prior Foreign Application Number(s) P. Hei. 11-215521 P. Hei. 11-215522 Additional foreign application application in the benefit under the second in the sec	Japan Japan Japan Japan Japan Japan Japan	ry foreign application for patent which priority is daimed. Foreign Filling Date (MM/DDAYYY) July/29/ 1999 July/29/ 1999 Juney/29/ 1999 mental priority sheet attached hereign Filling Date (MM/DDAYYYY)	Priority Not Claimed	YES NO X X X X X X X X X				
below and have also identified application having a filing date. Prior Foreign Application Number(s) P. Hei. 11-215521 P. Hei. 11-215522 Additional foreign application application in the benefit under the second in the sec	Japan Japan Japan Japan Japan Japan Japan	ry foreign application for patent which priority is daimed. Foreign Filling Date (MM/DDAYYY) July/29/ 1999 July/29/ 1999 Juney/29/ 1999 mental priority sheet attached hereign Filling Date (MM/DDAYYYY)	Priority Not Claimed	YES NO X X X X X X X X X				

[Page 1 of 5]
Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231.

DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS, SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231.

rase type a plus sign (+) inside this box	L	are required to	respond	F i lo a coi	Patent and Tri lection of info	ademark Off	ce: U.S. D	EPARTM	198. OMS	82/01 (8-96) 3 0651-0032 COMMERCE ntrol number.
DECLARATION										
I hereby claim the benefit under Title designating the United States of Amprior United States or PCT Internacknowledge the duty to disclose became available between the filing	erica, Ested below ational application information which	vand, insolara n in the man n is material to	is the su ner prov	bject ma ided by ablity as	tter of each o the first par defined in T	f the chaims agraph of Inte 37, Coo	of this appl Title 35, to le of Fede	ication is United Si ral Regu	not disclotales Cod tales Cod tations §1	le §112, I
U.S. Parent Application Number	PC	CT Parent Number		Par	ent Filing	Date		arent P	atent Ni o <i>plicab</i> i	
As a named inventor, I hereby appo								all busine	ess in the	Palent
and Trademark Office connected the	rewith:	Registrati Numbe	on			Name			Reg	istration umber
Charles B. Gordon 16923 Howard G. Shimola 26232 William C. McCoy, Jr. 16885 Jeffrey J. Sopko 27676 Richard H. Dickinson, Jr. 18622 John P. Murtaugh 34226 Thomas P. Schiller 20677 James M. Moore 32923 David B. Deioma 22841 David E. Spaw 34732					7676. 4226 2923					
Additional registered practitioner(s) named on a supplemental sheet attached hereto.										
Direct all correspondence to:										
Name Pearne, Gordon, McCoy & Granger L.L.P.										
Address 1200 Leader	Building	7								
Address Cleveland				0	tate	Ohio.	T	ZIP	441	1 4
	Ta	elenhone	(216							
I hereby declare that all statements	Country U.S. Telephone (216) 579-1700 Fax (216) 579-6073 I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that wilful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of									
Name of Sole or First Inve	ntor:				A petition ha	is been file	d for this	unsigne	d invento) r
Given Name Takahir	·o	Middle Initial		Family Name	HA	YASHI		I	Suffix e.g. Jr.	
Inventor's Signature Takas	hiro 9	Hay	asi	hù			Date	Feb	ruar	y 26, 2001
	agawa (Ssylle	1	untry		apan		Citiz	enship	JP
	-28, Wakak nagawa 227				, Yokoh	ama-sh	i,			
Post Office Address										
city Kanagawa	State	Zīp			Country		Japai	n		
X Additional inventors are	being named	d on supple	mental	sheet	(s) attache	d hereto		<u> </u>		· · · · · · · · ·

se type a plus sign (+) inside this box \rightarrow er the Paperwork Reduction Act of 1995, no p	ersons are re	quired to res	pond to a col	atent and Tra	Approved for use the demark Office: U.S., mation unless & conf	rough 9/30/98. ON DEPARTMENT OF	COMMERCE
DECLARA					DDITIONAL II Supplemer	VENTOR(S)	
Name of Additional Joint Inventor	r, if any:		A pet	ition has be	en filed for this uns	igned inventor	
Given Name Tetuya	Midd		Family Name		KUBO	Sur	mx
Inventor's Signature Jetuyi		Du.	lu		Date	February	26, 2001
Residence: Kanagawa		tate	Country	Ja	apan	Citizenship	JР
Post Office Address 6-36, Kik Kanagawa				-ku, Yo	okohama-shi	,	
Post Office Address				1			
City Kanagawa	State	Zip		Country		pan	
Name of Additional Joint Invento	or, if any:		A pe	tition has b	een filed for this ur		stlx
Siven Name	Initia		Name				
Inventor's Signature					Date		
Residence: City		State	Country			Citizenship	
Post Office Address							
Post Office Address							
City	State	Zip		Country			
Name of Additional Joint Invent				etition has b	een filed for this u		a1
Given Name	1	Middle Initial	Family Name			Suf r.a.	l l
Inventor's Signature					Date		
Residence: City		State	Country			Citizenshi	ip
Post Office Address	L.12.17						
Post Office Address							
City	State	ZIp		Country		· · · · · · · · · · · · · · · · · · ·	
Name of Additional Joint Invento	or, if any:	Middle	Family	etition has	been filed for this t		rtix
Given Name		Initial	Name				Jr.
Inventor's Signature					Date		
Residence: City		State	Country			Citizensh	p
Post Office Address	•						
Post Office Address							
City	State	ZIp		Country			
Additional inventors are being	g named c	on supple	mental she	et(s) attac	hed hereto		

2.

fer the Paperwork Reduction Act of 1	1995, no persons are required	d to respond to a		Trademark Office: formation unless I			
DECLARATION				PRIORITY DATA (Supplemental Sheet)			
Additional foreign applicatio	ns:						
rior Foreign Application Number(s)	Country		Filing Date	Priority Not Claimed	Certified Cop YES	y Attached? NO	
				000000000000000000000000000000000000000			
Additional provisional appli	cations: on Number		***	Filing Dato /h	MM/DDYYYY)		
Additional U.S. applications:		······································					
U.S. Parent Application Number		PCT Parent Number		iling Date	Parent Patent Number (if applicable)		

Picase type a plus sign (+) inside this box → +

PTO/SB/01 (3-96)

Approved for use through 9/30/98. CMB 0651-0332

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless 1 contains a valid CMB control number.

REGISTERED PRACTITIONER **DECLARATION** INFORMATION

DECLARATI		(Supplemental Sheet)			
Name	Registration Number	Name	Registration Number		
Paul R. Katterle Richard H. Mescher	36563 38242				

[Page 5 of 5]